Model 376 Windscreen for Microphones



General Description

The Electro-Voice® Model 376 Windscreen has been developed for use with the Electro-Voice ball type microphones. These include the following current products: RE50, N/D967, N/D767a, N/D367s, N/D267a, N/D267as, RE410, and RE510. The 376 Windscreen is also for use with the following legacy products: DS35, 1776A, 1777A, 671A, PL95, PL77A, PL76A, PL80, PL91A, RE11, RE16, and PL11. The 376 serves as a pop filter on the RE11, RE16, and PL11, which require covering of the slotted tubes for full windscreen protection.

The Model 376 Windscreen is fabricated of Acoustifoam[™], a material specifically developed for this use. Unique opencell Acoustifoam[™] material adds additional protection against dust, magnetic particles, moisture, etc., while also performing its primary function of screening out wind noise and annoying p-pops.

There is minimal signal attenuation caused by using the Model 376, and it is only noticeable above 10 kHz. The directional characteristics of the microphones are unaffected.

Installation

The Model 376 is designed to fit snugly over the microphone. To install, stretch windscreen over the ball portion of the microphone and slip into position. The Acoustifoam[™] material will shrink tightly into position in only a few seconds. A snug fit is all that needs to be checked.

Important Note:

The 376 should be washed periodically with a mild soap and warm water in order to maintain the porosity of the AcoustifoamTM.


Specifications subject to change without notice.



Technical Specifications:

Material:	Acoustifoam™
Color:	Gray
	RE50, N/D967, N/D767a, N/D367s, N/D267a, N/D267as, RE410, RE510
	DS35, 1776A, 1777A, 671A, PL95, PL77A, PL76A, PL80, PL91A, RE11, RE16, PL11
Dimension, Length:	97 mm (3.80")
Dimension, Diameter:	70 mm (2.76")
Net Weight:	7 g (0.25 oz.)

Dimensions:





12000 Portland Avenue South, Burnsville, MN 55337 Phone:952/884-4051, Fax:952/884-0043

www.electrovoice.com

© Telex Communications, Inc. 6/2006 Part Number 53607 Rev C U.S.A. and Canada only. For customer orders, contact Customer Service at: 800/392-3497 Fax: 800/955-6831

Europe, Africa, and Middle East only. For customer orders, contact Customer Service at: +49 9421-706 0 Fax: +49 9421-706 265

Other International locations. For customer orders, contact Customer Service at: + 1 952 884-4051 Fax: + 1 952 736-4212

For warranty repair or service information, contact the Service Repair department at: 800/553-5992 or 402/467-5321

For technical assistance, contact Technical Support at: 800/392-3497 or 952/736-4656